

H10G-V series

10" three-part filter housings for cold water with drain valve

General Description:

AQUAFILTER FHPRx-3VS, FHPRNx-3VS, FHPRx-3V R FHPRNx-3V_R - 10" three-part-type filter housings offer the versatility to meet all of customer filtration needs.

FHPRx-3VS, FHPRNx-3VS, FHPRx-3V R FHPRNx-3V R are dedicated for cold water on residencial or commercial

This housing can be used in as commercial setting due to its high flow efficiency. Filter housing consists of: a sump, ring and head with brass 1/2", 3/4" 1" inlet/outlet inserts and brass drain valve

Heads are equipped with a pressure relief valve (providing ability to release air pressure collected during cartridge replacement procedure). Filter housing is equipped with a drain valve enabling flushing sediments from the housing without removing filter cartridge (applicable with multi-use cartridges FCPNN series).

The tri-part design ensures maximum leak proof performance and ease of filter cartridge replacement.

A transparent cover allows for the evaluation of cartridge contamination

The FHPRx-3VS, FHPRNx-3VS, FHPRx-3V R FHPRNx-3V_R series housings can be mounted individually or connected in a series.

The FHPRx-3V_R series housings were tested and certified by NSF for structural integrity and material requirements.

Features:

- High quality
- Competitive Pricing
- Factory Tested
- Domestic and commercial use Three-part design (ideal connection stability)
- Equipped with filter bracket, wrench and drain valve*
- Equipped with antibacterial and antimicrobial filter cartridge centralizing ring*
- Made in EU with High Preformance Components
- NSF certified for structural integrity and material requirements**
- WRAS certificate*
- FDA CFR Title 21 Compliance
- Ideal for POU and POE use
- Maintenance Free -Saves \$, Time and Labor
- Easy to connect to cold water inlet
- Easy to install, No Electricity, No Drain Required
- Full flow 1/2", 3/4" or 1" ports
- * only in FHPRx-3V_R, FHPRNx-3V_R ** FHPRx-3VS, FHPRx-3V_R

Applications:

- Domestic istallations
- Pre-filtration systems - Food industry
- Industry laboratories

To FHPRx-3V series housing an antibacterial centering ring is added. TOTALLY FREE OF CHARGE!



Part Nr.	Size
FHPR12-3VS	1/2"
FHPR34-3VS	3/4"
FHPR1-3VS	1"



Part Nr.	Size
FHPRN34-3VS	1/2"
FHPRN34-3VS	3/4"
FHPRN1-3VS	1"

Below items sold as set include: filter housing, mounting bracket, wrench, cartridge centralizing ring and color box.



Part Nr.	Size
FHPR12-3V_R	1/2"
FHPR34-3V_R	3/4"
FHPR1-3V_R	1"



Part Nr.	Size
FHPRN12-3V_R	1/2"
FHPRN34-3V_R	3/4"
FHPRN1-3V_R	1"



This Cartridge is Tested and Certified by NSF Internation against NSF/ANSI Standard 42 for materials requirements only.

COMPONENT







H10G series

10" three-part filter housings for cold water with drain valve

Additional accessories







FXWR3-BL Wrench







OR-N-890X30 NBR O-ring he H10G housing:




FCPNNxM Multi-use sediment filter cartridges (nylon mesh)


Part Nr.	Size
FCPNN20M	20 mic.
FCPNN50M	50 mic.
FCPNN100M	100 mic.
FCPNN150M	150 mic.

Specifications:

Housing (sump): poly(ethylene terephtalate) (PET)

Housing (sump): poly(ethylene terephtalate) (PET)
Cap: polypropylene
Ring: polypropylene
Inserts: brass
Pressure relief valve: brass
O-ring: NBR
Thread: 1/2", 3/4", 1" BSP
Operating Pressure: 6 bar (90 psi)
Minimum working temperature: 2°C (35°F)
Maximum working temperature: 45°C (113.00°F)*
Dimensions without bracket (H x W x L): 445 x 105 x 120 (mm)
Cartridge dimensions: 9 7/8" x 2 1/2"









Part Nr.	Size
FCPNN20M	20 mic.
FCPNN50M	50 mic.
FCPNN100M	100 mic.
FCPNN150M	150 mic.

- NOTE

 Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

 Water filtration systems can help reduce the presence of contaminants. In addition, some water filtration systems can help reduce the presence of microorganisms or other contaminants with potential health effects.

 We strongly recommend regularly scheduled maintenance and replacement of the filter cartridge in order for the product to perform properly.

 Replace the filter cartridge at least every 6 or 12 months (depending on water quality and water consumption)

 LIMITED WARRANTY: Manufacturer warrants that this product is free from defects in materials and workmanship. This warranty, together with any and all warranties implied by law, shall be limited to a period of five (5) years from the date of original purchases

of original purchase.
This imitted warranty does not apply to failures that result from abuse, misuse, alteration or failure to properly comply with installation, or cartridge change instructions.
We strongly recommend adding to all point of use and point of entry a Pressure Limiting Valve to guard against unwanted extreme water pressure events pressure increases, surges, and water hammer which could occur in the water pipes.
Not having one installed could mean that if you ever did have to claim damage caused by a burst water filter system, the claim will be denied.

All Aquafilter images, trademarks, logos, and other intellectual property are the sole and exclusive property of Aquafilter, Inc. and may not be used without our express written permission



Aquafilter Made in EU **Facility**











91-222 Lodz, Poland

de@aquafilter.com









us@aquafilter.com

















^{*} Tested and certified by WRAS for 23°C only