



The Clear Choice
Water Filtration Systems

www.aquafilter.com

AISTRO-2-TW

2,5" Speciality in-line TWIST TYPE iron removing and water softening filter cartridge

General Description:

AQUAFILTER AISTRO-2-TW are state-of-the-art water softening and iron removal cartridges. They were designed to fit white 2.5" in-line **TWIST TYPE** housing.

AISTRO-2-TW was designed to allow optimal contact between water and the resin, therefore ensuring maximum performance (ion exchange). **AISTRO-2-TW** contains FDA-grade sodium-based strongly acidic ion-exchange resin which softens water (reduces calcium and magnesium content) and lowers the concentration of iron in water.



AISTRO-2-TW features easy twist-off filter four stage 1/4 turn encapsulated cartridge, all designed to make installation and replacement quick, easy and sanitary.

Once the filter is installed in place, there are no extra steps required. Just turn on the water to get it softened. Cartridges include pre- and post-filters preventing media particles from being washed out.

Each cartridge is pressure tested.


Features:

- High quality
- Competitive Pricing
- Made of safe, food grade materials
- Cartridges are removed with a simple 1/4-turn
- High capacity FDA Compliant ion-exchange resin
- Reduces scale formation
- Removes iron ions
- Made in EU with High Quality materials
- Cartridges are attractively labeled
- Easy Cartridge Replacements!



CAT #	Size	Max. Flow		Filter life* months
		lpm	gpm	
AISTRO-2-TW	12" x 2.5" (313 mm x 67 mm)	2.8	0.75	3 - 6
AISTRO-2-TW-CP	12" x 2.5" (325 mm x 82 mm x 14 mm)	2.8	0.75	3 - 6
AISTRO-2-TW-CP2	12" x 2.5" (338 mm x 82 mm x 14 mm)	2.8	0.75	3 - 6

* filter cartridge lifetime based on contamination level of potable water.



Made in EU

NOTE

- Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.
- We strongly recommend regularly scheduled maintenance and replacement of the filter cartridge in order for the product to perform properly.
- Replace the filter cartridge at least every 3 or 6 months (depending on water quality).
- Water filtration systems can help reduce the presence of contaminants. In addition, some water filtration systems can help reduce the presence of microorganisms or other contaminants with potential health effects.

LIMITED WARRANTY: AQUAFILTER warrants that this product is free from defects in materials and workmanship. This limited warranty does not apply to failures that result from abuse, misuse, alteration or failure to properly comply with installation or cartridge change instructions and water quality.

All Aquafilter images, trademarks, logos, and other intellectual property are the sole and exclusive property of Aquafilter, Inc. and may not be used without our express written permission.

**Aquafilter
Manufacturing
Facility**



Aquafilter Inc.
Hunt Valley 21030, USA
us@aquafilter.com



Aquafilter Germany
15234 Frankfurt, Germany
de@aquafilter.com



Aquafilter Europe
91-222 Lodz, Poland
pl@aquafilter.com

