



**The Clear Choice**  
Water Filtration Systems

[www.aquafilter.com](http://www.aquafilter.com)

# AIMIAO2\_K

**Mechanical leak prevention sensor, used to undercounter and reverse osmosis systems**

## General Description:

Damage caused by a leakage is one of the most common reason people make claims on their home insurance.

Even with an annual inspection, careful routine maintenance you might experience potentially very expensive flooding. Help protect your home and save the time and money with **AIMIAO-2\_K** mechanical leak prevention sensor.

This mechanical sensor is mostly used to undercounter and reverse osmosis systems. In the event of detection a small amount of liquid, it cuts off water, which flows to the filter and protects your home and wallet from unwanted and unexpected expenses caused by a flooding.

## Features:

- High quality
- Competitive Pricing
- Quick delivery
- Effectively protects against flooding
- Do not requires electrical connection



How AIMIAO2\_K works

# AIMIAO-T\_K

**Meter valve**

## General Description:

These unique meter valves provide automatic shut off of a potable water system for filter replacement after a pre-determined quantity of water has been filtered.

Meter valve provides automatic shut off for your home water filtration system. Designed with quick and easy installation, the meter valve will ensure proper performance and maintenance of your home water treatment system. Simple turn dial setting allows you to set the meter anywhere between 250 and 6,000 liters in 250 liters increments. Once activated, resetting the valve is completed through simply turning the dial back to your desired setting.

## Features:

- 6000 Liters capacity
- Easily reset to any capacity in increments of 250 liters
- Accuracy within 10% of setting
- Operating pressures from 1bar to 6bar
- Burst pressure tested to 25 bar
- Manufactured using NSF listed materials
- Available in black color

## Specifications:

- Standard 1/4" male NPT molded threads, 1/4" JACO Nut
- Housings Materials Nylon
- Operating Conditions Accuracy +/- 10 %
- Maximum Pressure 8 bars
- Factory preset for 3 liters per minute flow rate
- 6000 Liters Capacity
- Dimensions: 95mm H, 65mm W, 65mm D
- Working Temp.: 2°C (35°F) - 23°C (73.4°F)



Aquafilter Flow Meter Valve  
1/4" JACO Male NPT Fittings

All Aquafilter images, trademarks, logos, and other intellectual property are the sole and exclusive property of Aquafilter, Inc. and may not be used without our express written permission.

\*\*Picture is representative and may vary slightly from the actual product

**Aquafilter  
Manufacturing  
Facility**



**Aquafilter Inc.**  
Hunt Valley 21030, USA  
[us@aquafilter.com](mailto:us@aquafilter.com)



**Aquafilter Germany**  
15234 Frankfurt, Germany  
[de@aquafilter.com](mailto:de@aquafilter.com)



**Aquafilter Europe**  
91-222 Lodz, Poland  
[pl@aquafilter.com](mailto:pl@aquafilter.com)

